इचलकरंजी महानगरपालिका, इचलकरंजी

कार्यक्रम पत्रिका क्र. (६/२०२६)
स्थायी समिती सभा

दिनांक- ०३/०७/२०२६

प्रति.

मा. ----------
स्थायी समिती सदस्य / सदस्या,
इचलकरंजी महानगरपालिका, इचलकरंजी

महोदय,

इचलकरंजी महानगरपालिका मा. स्थायी समिती सदस्य यांना नोटीस देणेत येते की इचलकरंजी महानगरपालिका स्थायी समितीची सभा सोमवार दि. ०६/०७/२०२६ रोजी दुपारी १२.१५ वाजता इचलकरंजी महानगरपालिकेच्या प्रशासकीय इमारतीतील स्थायी समिती सभागृह येथे भरविणेत येत आहे.

तरी सदर सभेस उपस्थित राहणेबद्दल आपणास विनंती करणेत येत आहे.

(प्रतिश वसंतराव मुळीक)
सभापती,
स्थायी समिती

****

परिशिष्ठ

विषय क्र(१): मागील सभा दि. १५/०६/२०२६ रोजीच्या सभेचे इतिवृत्त कायम करणे.

विषय क्र(२): सदस्य स्वेच्छा निधीतून इचलकरंजी महानगरपालिका शौचालय / गटर / इमारती रंगरंगोटी / शाळा / व्यायाम शाळा साहित्य दुरुस्ती करणे व इतर अनुषंगीक विकास कामे करणे करीता एकूण १०४ बाबींचे करणेत आलेले अंदाजपत्रकास (Rate Contract) मंजुरी देणेबाबत कार्यालयाकडुन आलेला प्रस्ताव.

विषय क्र(३): इचलकरंजी महानगरपालिका हद्दीमधील दैनंदीन बाजार फी, मंडप / स्टॉल भाडे वसुली मक्ता देणेकामी आधारभुत किंमत १,३१,५६,०००/- याजवर दोन वेळा निविदा मागविणेत आली असता निविदेस प्रतिसाद मिळत नसलेने उत्पन्न वाढीचे दृष्टीने सन २०२३-२४ या सालामधील धरलेली आधारभुत किंमत रु. ९४,००,०००/- गृहीत धरुन नव्याने निविदा प्रसिद्ध करणेस मंजुरी मिळणेबाबत कार्यालयाकडुन आलेला प्रस्ताव.

विषय क्र(४): इचलकरंजी महानगरपालिकेकडे रोगजंतुनाशके व औषधी द्रव्ये यांचा पुरवठा करणे अंदाजपत्रक र. रु. १,०१,४०,०००/- व इचलकरंजी महानगरपालिकेकडे रोगजंतुनाशके / डास अळी नाशके / किटकनाशके व औषधी द्रव्ये यांचा पुरवठा करणे अंदाजपत्रक र. रु. ४८,८६,८००/- यास मंजुरी देणेबाबत कार्यालयाकडुन आलेला प्रस्ताव.

विषय क्र. ५ : मा.सभापती यांचे परवानगीने घेणेत येणारे ऐनवेळचे इतर विषय.

Scanned with OKEN Scanner

इचलकरंजी महानगरपालिका

मा. स्थायी सभा क्र.०६ स्था. स. ठराव क्र. 33
दि. ०६/०७/२०२६

विषय क्र. २ : सदस्य स्वेच्छा निधीतून इचलकरंजी महानगरपालिका शौचालय / गटर / इमारती रंगरंगोटी / शाळा / व्यायाम शाळा साहित्य दुरुस्ती करणे व इतर अनुषंगीक विकास कामे करणे करीता एकूण १०४ बाबींचे करणेत आलेले अंदाजपत्रकास (Rate Contract) मंजुरी देणेबाबत कार्यालयाकडुन आलेला प्रस्ताव.

ठराव

इचलकरंजी महानगरपालिका शौचालय / गटर / इमारती रंगरंगोटी / शाळा / व्यायाम शाळा साहित्य दुरुस्ती करणे व इतर अनुषंगीक विकास कामे करणे कामी इचलकरंजी महानगरपालिकेचे सर्वसाधारण सभा दि. २७/०३/२०२५ ठराव क्रमांक ४० प्रमाणे महानगरपालिकेच्या प्रत्येक सदस्यांसाठी रु. ७.५० लाख व महापौर उपमहापौर, सभागृह नेता, विरोधीपक्ष नेता यांना प्रत्येकी र.रु. ५० लाख याप्रमाणे स्वेच्छा निधी मंजूर करण्यात आला असून त्यास सदस्य स्थानिक विकास निधी असे संबोधण्यात आले आहे. त्याचे वापराबाबत दि. ३०/०४/२०२६ चे महासभेमध्ये कार्यपद्धती निश्चित करणेत आली आहे.

वरील सर्व प्रकारचे कामांसाठी ॲटम प्रमाणे वार्षिक दर निश्चित करून समान दराने काम करणेस तयार असणाऱ्या एक वा एकापेक्षा अनेक मक्तेदारांकडून वार्षिक कामाचे दर करार करणेत येणार आहेत.

उपरोक्त कामांची मागणी संबंधित सदस्यांद्वारे लेखी पत्राद्वारे आयुक्तांकडे करण्यात आलेनंतर आयुक्त संबंधित विभाग प्रमुखास यासंदर्भात आदेशित करतील, कामाची पाहणी करून आवश्यकतेनुसार अंदाजपत्रक करून वार्षिक दर कराराचे मक्तेदारास सदरचे काम पूर्ण करण्याबाबत कार्यादेश देण्यात येतील,

दि.३०.०४.२०२६. च्या महासभेचे मान्यतेनुसार विकास कामे जलद गतीने व गुणवत्ता पुर्वक होणे साठी एकूण १०४ बाबींचा समावेश केला आहे.

नगरसेवक स्वेच्छा निधी व पदाधिकारी विशेष स्वेच्छा निधी या लेखाशिर्षाशी संबधीत सन २०२६-२७ नगरसेवक स्वेच्छा निधी व पदाधिकारी विशेष स्वेच्छा निधी या लेखाशिर्षकात खर्ची करून निविदा मागवता येईल. विषयांकित काम हे आवश्यक असलेने सदर काम नगरसेवक स्वेच्छा निधी व पदाधिकारी विशेष स्वेच्छा निधी या लेखाशिर्षात सन २०२६-२७ या अर्थिक वर्षामध्ये खर्च पडणार आहे.

कामाचे नांव	नगरसेवक स्वेच्छा निधी व पदाधिकारी विशेष स्वेच्छा निधी

सदरबाबत कार्यालयाने खालीलप्रमाणे १०४ आयटमचे दर निश्चित केले आहेत.

अ. क्र.	ज्या बाबींसाठी दर द्यावयाचा आहे त्याचा तपशील	यूनिट	SSR/ मार्केट दर सर्व Lead, Lift, वाहतुकसह
1	Excavation for foundation in earth, soil of all types, sand, gravel and soft murum, including removing the excavated material up to a distance of 50 metre beyond the building area and stacking and spreading as directed, dewatering, preparing the bed for the foundation and necessary back filling, ramming, watering including shoring and strutting excetra complete. - (Lift upto 1.5 metre) By Manual Means	CU.M	250.7
2	Hire charges for Excavator (JCB JS 140 / TATA Hitachi EX 120 or equivalent) - 0.6 Cum capacity at the site of work	HOUR	1752.45
3	Excavation for catch / side water gutter in all sorts of soils to specified section including stacking excavated stuff in regular bund & disposing off unsuitable or excess stuff.	CU.M	124.85
4	Excavation for roadway in earth, soil of all sorts, sand, gravel or S.M. including dressing section to required grade, camber & side slopes & conveying excavated materials with all lifts upto lead of 50 m & spreading for embankment or stacking as directed. - By Manual Means	CU.M	314.7
5	Dismantling stone masonry in lime or C.M. including stacking materials as directed with all leads, lifts etc. complete.	CU.M	398.6
6	Dismantling brick masonry in lime or cement mortar and stacking the materials as directed with all leads, lifts excetra complete.	CU.M	351.4
7	Removing lime or lean cement concrete including stacking the spoils as directed with all leads, lifts excetra complete.	CU.M	585.35
8	Conveying materials obtained from excavation.(murum ,building, rubished, earth) lead 3000 meter, page no 559.	CU.M	220
9	Providing soling using 80 milimetre size trap metal in 15 centimetre layer including filling voids with crushed sand / grit, ramming, watering, excetra complete.	CU.M	2089.1

Scanned with OKEN Scanner

10	Providing dry trap/ granite/ quartzite/ gneiss rubble stone soiling 15 centimetre to 20 centimetre thick including hand packing and compacting, excetra complete.	CU.M	2050.45
11	Supplying hard murum / kankar at the road site, including conveying and stacking, excetra complete.	CU.M	787.1
12	Spreading hard murum / soft murrum / gravel or kankar for side width, excetra complete.	CU.M	82.85
13	Compacting the hard murum side widths including laying in layers on each side with vibratory roller including artificial watering, excetra complete.	SQ.M	22.05
14	Providing selected hard murum filling including laying in layers of 15 centimetre to 20 centimetre, watering and compacting, excetra compelte.	CU.M	1023.1
15	Providing and fixing heavy duty inter locking concrete coloured paving blocks of 60 milimetre thickness of having a strength of 300 kilogramme per square centimetre of approved quality and shape on a bed of crushed sand of 25 milimetre to 30 milimetre thick including striking joints and cleaning, excetra complete.	SQ.M	974.3
16	Providing second class Burnt Brick masonry with conventional / Indian Standard type bricks in cement mortar 1:6 superstructure including striking joints, racking out joints, watering and scaffolding, excetra complete. (For Ground Floor) (using ARTIFICIAL SAND).	CU.M	9069.7
17	Providing internal cement plaster 12 milimetre thick in a single coat in cement mortar 1:4 without neeru finish to concrete or brick surfaces, in all positions including scaffolding and curing, excetra complete. (For Ground Floor) (using ARTIFICIAL SAND).	SQ.M	296.05
18	Providing sand faced plaster externally in cement mortar using approved screened sand in all positions including base coat of 15 milimetre thick in cement mortar 1:4 using waterproofing compound at one killogramme per cement bag curing the same for not less than 2 days and keeping the surface of the base coat rough to receive the sand faced treatment of 6 to 8 milimetre thick in cement mortar 1:4 finishing the surface by taking out grains and curing for fourteen days, scaffolding, excetra complete. (For Ground Floor) (using ARTIFICIAL SAND).	SQ.M	680
19	Providing and fixing Orissa type white glazed eartthenware 575 milimetre water closet pan including "S" trap with earthenware foot rests, cast iron soil and vent pipe upto outside face of the wall, 1:2:4 brick bat lime concrete bedding without flushing tank and its accessories excetra complete. (For Ground Floor)	NO	4203.35
20	Providing and fixing European type white glazed earthenware coupled closet symphonic trap with symphonic low level white glazed 10 litres cistern with black backlite seat with all necessary pipe connection, excetra complete. (For Ground Floor)	NO	11748.8
21	Providing and fixing white glazed earthenware wash hand basin of 45 centimetre X 30 centimetre size including cold water piller tap / cold and hot water piller tap brackts, rubber plugs and brass chain, stop tap and necessary pipe connections including polyvinyl chloride waste pipe and trap upto the outside face of the wall.Making good thedamaged surface, testing excetra complete. (For Ground Floor)	NO	6031.75
22	Providing and fixing white glazed earthenware lipped flat back / corner type urinal with polyvinyl chloride 5 litres flushing cistern with fitting inlet pipe and stop tap, brackets for fixing the cistern 32 milimetre diameter polyvinyl chloride flush pipe with fitting including lead soil pipe, lead trap and soil pipe connection upto the outside face of the wall. (For Ground Floor)	NO	5022.6
23	Providing and fixing White Glazed Earthenware Squatting plate (Ladies Urinal) with polyvinyl chloride flushing cistern of 5 liters capacity with fitting, inlet pipes and stop tap, brackets for fixing the cistern, 32 milimetre diameter P.V.C flush pipe with fittings and flushing arrangement including lead soil pipe, lead trap, soil pipe connection up to the outside face of the wall. (For Ground Floor)	NO	4377.5
24	Providing and fixing sheet glass of 24 oz. for all size including putty, excetra complete. (For Ground Floor)	SQ.M	1046.9
25	Providing and fixing solid core flush door shutter in single leaf 32 milimetre thick decorative type of exterior grade as per detailed drawings, approved face veneers 3 milimetre thick on both faces or as directed, all necessary beeds, moulding and lipping, wrought iron hold fasts, chromium plated fixtures and fastenings, with brass mortise lock, chromium plated handles on both sides and finishing with french polish, excetra complete. (For Ground Floor)	SQ.M	3229.85
26	Replacement of damaged aldrop 300 milimetre iron oxidised of approved quality and make to door shutter including removing existing the same in original position making proper adjustment for smooth operation, excetra complete as per sample approved by Engineer in-charge. (For Ground Floor)	No	337.8
27	Replacement of damaged aluminium butt hinges of 125 milimetre of approved quality and make to door shutter including removing existing the same in original position making proper adjustment for smooth operation , excetra complete as per sample approved by Engineer incharge. (For Ground Floor)	No	309.45

Scanned with OKEN Scanner

28	Providing and fixing M-40 grade thick vibrated pull cast or similar type concrete frame with chamfer confirming to Indian Standard : 6524-1983 having 6 milimetre diameter bars three numbers and stirrups at 250 milimetre center to center and fixing in wall with six numbers of holdfast of 12 milimetre diameter bars 500 milimetre long including primer and oil painting, excetra complete. - Frame size 60 milimetre X 125 milimetre. (For Ground Floor)	RMT	1200.05
29	Providing and applying two coats of exterior weather shield paint of approved manufacturer and of approved colour to the plastered surfaces including cleaning, preparing the plaster surfaces, applying primer coat, scaffolding, if necessary and watering the surface for two days, excetra complete. (For Ground Floor)	SQ.M	309.45
30	Providing and applying washable oil bound distemper of approved colour and shade to old and new surfaces in two coats including scaffolding, preparing the surfaces (excluding the primer coat), excetra complete. (For Ground Floor)	SQ.M	50.35
31	Providing & applying priming coat on concrete / masonary / A.C. / plastered surfaces including scaffolding if necessary, preparing surface by thoroughly cleaning oil, grease, dirt & other foreign matters & sand papering as required. (For First Floor)For Ground Floor (For Ground Floor)	SQ.M	37.75
32	Providing and applying two coats of flat oil paint of approved colour to the old structural steel work and iron work previously painted in building including scaffolding, if necessary, cleaning and preparing the surface (excluding primer coat), excetra complete. (For Ground Floor)	SQ.M	89.15
33	Providing and applying Royale Luxury Emulsion of approved make on internal wall surface as detailed below - Scrapping for surface with emery paper and wipe clean for area. Applying wall primer with brush by adding mineral turpentine oil by 8 to 10 percent or water by 15 to 20 percent allowing to dry for 6 to 8 hours. After applying approved make acrylic wall putty with appropriate proportion of water of allow to dry for period of 4 to 6 hours of activity. Scrapping with emery paper and wipe clean. Applying paints Royale Luxury emulsion first coat with brush water content water 40 to 45 percent or 65 to 70 percent by role. Applying paints Royale luxury emulsion second coat with brush with water content 40 to 45 percent or 65 to 70 percent by roller. (With prior approval of S.E.) (For Ground Floor)	SQ.M	288.5
34	Providing and laying concrete pipes of Indian Standard Non Pressure class of 225 milimetre diameter in proper line, level and slope including necessary collers, excavation, laying, fixing with collers in cement mortar 1:1 and refilling the trench excetra complete.	RMT	803.15
35	Providing and laying cement concrete pipe confirming to Indian Standard 458:2003 non pressure class-2 of 450 milimetre diameter in proper line, level and slope including providng and fixing collars in cement mortar 1:2 and curing, excetra complete.	RMT	2079.95
36	Providing and laying concrete pipes of Indian Standard Non Pressure class of 150 milimetre diameter in proper line level and slope including necessary collers, excavation, laying, fixing with collers in cement mortar 1:1 and refilling the trench complete.	RMT	555.95
37	Providing and laying cement concrete pipe of Indian Standard 458:2003 non pressure class-3 of 600 milimetre diameter in proper line, level and slope excetra complete.	RMT	5119.55
38	Providing and laying cement concrete pipe of Indian Standard 458:2003 non pressure class-3 of 900 milimetre diameter in proper line, level and slope excetra complete.	RMT	8842.4
39	Supplying reinforced cement concrete Pipe 450 milimetre diameter (NP3) 2.5 metre long at the site of work.	RMT	2250.3
40	Supplying reinforced cement concrete Pipe 700 milimetre diameter (NP3) 2.5 metre long at the site of work.	RMT	4463.05
41	Providing and laying in trenches 15 milimetre diameter chlorinated poly vinyl chloride pipe including necessary excavation, fittings, refilling trenches, excetra complete Including removing existing pipe line if necessary and conveying and stacking the same in PWD chowky or as directed excetra complete.	RMT	286.4
42	Providing and laying in trenches 20 milimetre diameter chlorinated poly vinyl chloride pipe including necessary excavation, fittings, refilling trenches, excetra complete. Including removing existing pipe line if necessary and conveying and stacking the same in PWD chowky or as directed excetra complete.	RMT	326.25
43	Providing and laying in trenches 25 milimetre diameter chlorinated poly vinyl chloride pipe including necessary excavation, fittings, refilling trenches, excetra complete. Including removing existing pipe line if necessary and conveying and stacking the same in PWD chowky or as directed excetra complete.	RMT	443.75
44	Providing and laying in trenches 50 milimetre diameter chlorinated poly vinyl chloride pipe including necessary excavation, fittings, refilling trenches, excetra complete. Including removing existing pipe line if necessary and conveying and stacking the same in PWD chowky or as directed excetra complete.	RMT	821.35
45	Providing, laying and fixing polyvinyl chloride pipe of 75 milimetre diameter with fittings such as bends, tees, reducers, clamps, excetra inclduding necessary excavation, trench filling, excetra complete.Including removing existing pipe line if necessary and conveying and stacking thesame in PWD chowky or as directed excetra complete.	RMT	452.1
46	Providing, laying and fixing polyvinyl chloride pipe of 110 milimetre diameter with fittings such as bends, tees, reducers, clamps, excetra including necessary excavation, trench filling, excetra complete.Including removing existing pipe line if necessary and conveying and stacking thesame in PWD chowky or as directed excetra complete.	RMT	623.1

Scanned with OKEN Scanner

47	Providing and fixing push cock (self closing tap) symet type of 15 milimetre diameter including necessary socket, testing, excetra complete. (For Ground Floor)	NO	476.25
48	Providing and fixing push cock (self closing tap) symet type of 20 milimetre diameter including necessary socket, testing, excetra complete. (For Ground Floor)	NO	488.85
49	Provoding and fixing high density polyethylen container one piece moulded water tank made out of high density polyethylen and built corrugated inclusive of delivery upto destination housting, fixing of accessaries such as inlet, outlet, overflow pipe inclusive of all Taxes. Capacity between 200 litres to 1000 litres. (For Ground Floor)	LIT	14.7
50	Providing and fixing in position anodised extruded aluminium partitions having frame made out of extruded tubular section of size 65 milimetre X 40 milimetre with 12 milimetre thick three layered flat pressed teak wood particle board bonded with boiling water proof type exterior grade phenol formaldehyde synthetic resin conforming to Indian Standard : 12923-1990, laminated on both sides, Novateak or equivalent with aluminium glazing clips of size 12 milimetre X 12 milimetre (conical) as per drawing, excetra complete. (For Ground Floor)	SQ.M	4162.45
51	Providing and fixing of colour coated zincalume (R) AZ 150 (Minimum 150 grams per square metre total on each sides) profiled sheets for roofing. The feed material is manufactured out of nominal 0.45 milimetre base metal thickness (BMT) (0.5 milimetre TCT), Hi-strength steel with minium 550 MPa yield strength, metallic hot dip coated with Aluminium-Zinc alloy (55 percent aluminium, 43.4 percent zinc, 1.6 percent silicon) with COLORBOND (R) steel quality super durable polyster paint coat (with inorganic pigment). The paint shall have a total coating thickness of nominal 35 um, comprising of nominal 25 um exterior coat on top surface and nominal 10 um reverse coat on back surface. Profile sheet shall have nominal 950-1050 milimetre effective cover width and nominal 25-30 milimetre deep ribs with subtle square fluting in the five pan at nominal 180-250 milimetre center to centre. The end rib shall be designed for anti capilary groove and return leg. The feed material should have coil manufacturer's product details marked at regular interval. Including fasteners with minium fatened with minium 25 um zinc-tin alloy coated, hex head, self-drilling screw, excetra complete. (Weight of profile 4.52 kilogram per square metre). (For Ground Floor)	SQ.M	1230.5
52	Providing and fixing 4 milimetre thick plain asbestos cement sheets of Indian Standard on top of the weather shed including scaffolding, fixing by means of nuts and bolts or as directed, excetra complete as per detailed drawing. (Brackets of 70 milimetre X 45 milimetre to be paid separately). (For Ground Floor)	SQ.M	680.8
53	Removing galvanised iron or asbestos cement sheet roofing including purlines, principal rafter excetra including sorting servicable and unserviceable materials, stacking the same as and where directed in the compound including scaffolding, excetra complete.	SQ.M	93.35
54	Providing and fixing Road junction / Information sign board of size 0.90 metre X 0.60 metre prepared on 16 gauge mild steel sheet with angle iron frame of size 35 milimetre X 35 milimetre X 5 milimetre including painting with one coat of zinc cromate stoving primer and two coats each of green/ white back ground and back side gray stove enamelled, bonded with red retro-reflective sheet Engineering grade, border / letters / numeral / arrows, coated with non pealable crystal clear protective coat retaining 100 percent reflection including two angle iron post of size 50 milimetre X 50 milimetre X 5 milimetre of 3.65 metre long inflated at bottom drilled on top and painted in white and black bands of 30 centimetre, with 4 numbers high strength galvanised iron bolts and nuts of size 10 milimetre diameter and 20 milimetre long sheet and angle iron post in one piece without joints including all taxes, conveying, fixing in ground with cement concrete 1:4:8 block of 60 centimetre X 60 centimetre X 75 centimetre size as directed by Engineer-in-charge, excetra complete. Mild Steel Board with Engineering Grade.	NO	8196.9
55	Painting with approved enamel paint in two coats including cleaning surface and lettering for Cautionary / mandatory sign boards and village name boards excetra complete.	SQ.M	212.95
56	Providing and laying ceramic tiles of having sizes 30 centimetre X 30 centimetre and confirming to corresponding Indian standared for dado and skirting in required position with ready made adhesive mortar of approved quality on plaster of 1:2 cement mortar including joint filling with white / colour cement slurry, cleanding, curing, excetra complete. (For Ground Floor) (using ARTIFICIAL SAND).	SQ.M	1367.85
57	Providing and laying matt finish ceramic tiles of having sizes 30 centimetre X 30 centimetre and confirming to Indian Standard 15622 : 2006 (Group DII-A) and 7 milimetre to 8 milimetre thick for flooring in required position laid on a bed of 1:4 cement mortar including cement float, filling joint with white / colour cement slurry, cleaning, curing, excetra complete. (For Ground Floor) (using ARTIFICIAL SAND).	SQ.M	1291.25
58	Providing and laying in position flooring of telephone black / amba white / cadbury brown / RBI red / ocean brown granite stone of approved shade and size 18 milimetre to 20 milimetre thick on a bed of 1:6 cement mortar including cement float, striking joints, pointing in cement mortar 1:3, curing and cleaning, excetra complete. (For Ground Floor) (using ARTIFICIAL SAND).	SQ.M	4230.2

Scanned with OKEN Scanner

59	Providing and laying polished Tandur stone Flooring 25 milimetre to 30 milimetre thick and of required width in plain / diamond pattern on a bed of 1:6 cement mortar including cement float, filling joints with neat cement slurry, curing, polishing and cleaning, excetra complete. (For Ground Floor) (using ARTIFICIAL SAND).	SQ.M	1139.85
60	Providing and laying telephone black / amba white / cadbury brown / RBI red / ocean brown granite stone of 18 milimetre to 20 milimetre thick for door frame / dado / window boxing, excetra on cement mortar 1:6 including filling joints with polymer base filler, nosing the sharp edges wherever necessary, curing, excetra complete. (For Ground Floor) (using ARTIFICIAL SAND).	SQ.M	4609.1
61	Providing and fixing Mangalore tiled roofing with class "AA" tiles including securing the last course of tiles near the eaves with steel flat 40 milimetre X 3 milimetre and 1.22 milimetre wire fixing 50 milimetre X 25 milimetre horizontal teak wood battens and iron works and oiling the battens, excetra complete. (excluding ridge and hip tiles) (For Ground Floor)	SQ.M	1240.95
62	Removing and resetting Mangalore tiles from roof including refixing loose battens, excetra complete. (For Ground Floor)	SQ.M	100.7
63	Providing and fixing country teak wood battens 50 milimetre X 25 milimetre for Mangalore tile roof work with all iron work, scaffolding and oiling the battens, excetra complete. (For Ground Floor)	SQ.M	130.1
64	Providing and fixing corrugated galvanised iron sheets of 0.63 milimetre thick (24 B.W.G) for roofing without wind tiles including fastening with galvanised iron screw and bolts and lead / bitumen washers as per drawing, excetra complete. (Weight 5.5 killogram per square metre) (For Ground Floor)	SQ.M	912.65
65	Providing and laying vitrified rustic matt stone finish tiles having size 590 milimetre to 605 milimetre X 590 milimetre to 605 milimetre of 8 milimetre to 10 milimetre thickness and confirming to Indian Standard 15622-2006 (Group BIa) of approved make, shade and pattern for flooring in required position laid on a bed of 1:4 cement mortar including neat cement float, filling joints, curing and cleaning, excetra complete. (For Ground Floor) (using ARTIFICIAL SAND).	SQ.M	1907
66	Providing and laying rough Shahabad stone flooring 25 milimetre to 30 milimetre thick and of required width in plain / diamond pattern on a bed of 1:6 cement mortar including cement float, striking joints, pointing in cement mortar 1:3, curing and cleaning, excetra complete. (For Ground Floor) (using ARTIFICIAL SAND).	SQ.M	775.85
67	Providing and laying damp proof course 50 milimetre thick in M-20 cement concrete layer and bitumen / using cement with waterproofing compound curing, formwork, excetra complete. (For Ground Floor) (using ARTIFICIAL SAND).	SQ.M	492.15
68	Providing Water proofing treatment to old terraces by removing existing treatment, sealing of cracks by non shrink crack fill compound applying first coat of polymer modified semi- viscous paste prepared by mixing polymer of approved make and cement in 1:2 proportion (one litre polymer : two kilogram cement) or Rohnex water proofing system in two coats(one kilogram powder, 700 mililitre water and polymer jelly for first coat and one kilogram powder, 500 mililitre water and polymer jelly for second coat) to a neatly cleaned and dust free concrete surface and upto 300 milimetre over parapet wall prepared by removing loose and deposited material with brush and water, followed by two coat of flexible cementious coating of approved make after laying glass fibre mesh of 10 X 10 specification of approved make over tacky surface of first coat of polymer followed by second coat in transverse direction, sprinkling coarse sand over it, followed by protective mechanical cover of 40 milimetre to 75 milimetre. thick cement concrete of 1:2:3 proportion using coarse aggregate of 10 MSA and water proofing compound of approved make along with 14 guage 40 milimetre X 40 milimetre size welded mesh and and polypropylene fibres at the rate of 125 gram per bag of cement within it conforming to Indian Standard in pannels of three metre / four metre or as per site condition and filling the joints with polt sulphide sealant(0.12 kilogram per sq.m.) after curing, including providing holler with drip moulds at the junction and finishing the concrete surface with neat cement slurry including curing as directed and ponding the surface as directed excetra complete; covering 10 years guarantee against leakproofness on Court Fee Stamp Paper of Rs. 100/-	SQ.M	2273.2
69	Providing and laying of hot applied thermoplastic compound 2.5 milimetre thick including reflectorizing glass beads at the rate of 250 grams per square metre area, thickness of 2.5 milimetre is exclusive of surface applied glass beads as per Indian Road Congress : 35. The finished surface to be level, uniform and free from streaks and holes complete.		698.65
70	Supply of all types of Structural steel conforming to Fe 410 B of Indian Standard : 2062, Fabrication, assembling, erection / slewing / end launching of Steel girders (not requiring traffic block) upto 45.7 metre span on sub structure including provision of trolley refuges, including loading, unloading, lift and taxes complete, assembly of girders on drift / bolts, field riveting / welding, assembling of temporary support for side slewing, raising of girders to the bed block level, providing sliding arrangements (Material at site, fabrication at site, erection / launching, excetra only) - Plate Girder / Semi Through Girder.	M.T.	112415.05
71	Providing and cutting, bending, hooking, ticing and laying in position thermo mechnically treated FE-500 steel bars for reinforcement for reinforcement for all reinforced cement concrete works as per detailed drawings, excetra complete.	M.T.	92669.7
72	Providing and constructing brick masonry inspection chamber 60 centimetre X 45 centimetre X 90 centimetre including 1:4:8 cement concrete foundation, 1:2:4 cement concrete channels, half round glazed stoneware pipes, brick masonry, plastering from inside and airtight cast iron lid 75 kilogram with frame fixed in cement concrete, excetra complete. (using ARTIFICIAL SAND).	NO	14718.45

Scanned with OKEN Scanner

73	Providing and laying Cast in situ/Ready Mix, cement concrete in M-10 of trap/ granite/ quartzite/ gneiss metal for foundation and bedding including bailling out water, formwork, laying/ pumping, compacting and curing, excetra complete, with fully automatic micro processor based Programmable Logic Controller without Supervisory Control and Data Aquisition enabled reversible Drum Type mixer/ concrete Batch mix plant (Pan mixer) excetra complete. With fine aggregate (Natural Sand / Crushed sand VSI Grade finely washed, excetra) (using ARTIFICIAL SAND). (using ARTIFICIAL SAND). (using ARTIFICIAL SAND).	CU.M	6562.4
74	Providing and laying Cast in situ / Ready Mix cement concrete M-15 of trap r bed blocks, foundation blocks and such other items including bailling out water, plywood / steel formwork, compacting, roughening them if special finish is to be provided, finishing uneven and honeycombed surface and curing, excetra complete. The cement mortar 1:3 plaster is considered for rendering uneven and honeycombed surface only. Newly laid concrete shall be covered by gunny bag, plastic, tarpaulin, excetra (Wooden centering will not be allowed.) with fully automatic micro processor based Programmable Logic Controller without Supervisory Control and Data Aquisition enabled reversible Drum Type mixer/ concrete Batch mix plant (Pan mixer) excetra complete. With fine aggregate (Natural Sand / Crushed sand VSI Grade finely washed etc) (using ARTIFICIAL SAND). (using ARTIFICIAL SAND).	CU.M	7084.45
75	Providing and laying Cast in situ / Ready Mix cement concrete M-20 of trap / granite /quartzite/ gneiss metal fo bed blocks, foundation blocks and such other items including bailling out water, plywood / steel formwork, compacting, roughening them if special finish is to be provided, finishing uneven and honeycombed surface and curing, excetra complete. The cement mortar 1:3 plaster is considered for rendering uneven and honeycombed surface only. Newly laid concrete shall be covered by gunny bag, plastic, tarpaulin, excetra (Wooden centering will not be allowed.)with fully automatic micro processor based Programmable Logic Controller without Supervisory Control and Data Aquisition enabled reversible Drum Type mixer/ concrete Batch mix plant (Pan mixer) excetra complete. With fine aggregate (Natural Sand / Crushed sand VSI Grade finely washed etc) (using ARTIFICIAL SAND). (using ARTIFICIAL SAND).	CU.M	7458.05
76	Providing and casting in situ or precast tapering reinforced cement concrete M-20 Barrier type kerb without gutter (as per Indian Road Congress : 86-1983) embedded 125 milimetre below ground level over M-10 plain cement concrete finished neatly with cement mortar 1:2, setting the same in cement mortar 1:2, including the required excavation in any strata and removing the excavated stuff any where in city and redoing the surface as specified and directed by Engineer in-charge. Using concrete batching and mixing plant.	RMT	581.15
77	Providing and laying cast in situ / Ready Mix cement concrete M-20 of trap metal for reinforced cement concrete plinth beams as per detailed drawings or chamfered as approved by the Engineer including centering, formwork, cover blocks, compacting, finishing and roughening the surface if special finish is to be provided and curing complete. (Excluding reinforcement, including cover block) Newly laid concrete shall be covered by gunny bag, plastic, tarpaulin excetra with fully automatic micro processor based Programmable Logic Controller without Supervisory Control and Data Aquisition enabled reversible Drum Type mixer/ concrete Batch mix plant (Pan mixer) excetra complete. With natural sand/V.S.I. quality Artificial Sand (using ARTIFICIAL SAND).	CU.M	7933.6
78	Providing and laying cast in situ / Ready Mix cement conrete M-20 of trap / granite /quartzite/ gneiss metal for reinforced cement concrete columns as per detailed designs and drawing or as directed, including steel centering, formwork, cover blocks,aying/pumping, compaction, finishing the formed surfaces with cement mortar 1:3 of sufficient minimum thickness to give a smooth and even surface or roughening the surface if special finish is to be provided and curing, excetra complete. (Excluding reinforcement and structural steel). with fully automatic micro processor based Programmable Logic Controller without Supervisory Control and Data Aquisition enabled reversible Drum Type mixer/ concrete Batch mix plant (Pan mixer) excetra complete.with fine aggregate (Natural Sand / Crushed sand VSI Grade finely washed etc) (For Ground Floor) (using ARTIFICIAL SAND).	CU.M	14849.65
79	Providing and laying cast in situ / Ready Mix cement concrete in M-20 of trap/ granite/ quartzite/ gneiss metal for reinforced cement concrete waist slab and steps of staircases as per detailed design and drawings or as directed including steel centering, plywood / steel formwork, steel props, compaction, finishing uneven and honeycombed surface with cement mortar 1:3 of sufficient minimum thickness to give a smooth and even surface or roughening the surface if special finish is to be provided and curing, excetra complete. (Excluding reinforcement, including cover block) Newly laid concrete shall be covered by gunny bag, plastic, tarpaulin excetra with fully automatic micro processor based Programmable Logic Controller without Supervisory Control and Data Aquisition enabled reversible Drum Type mixer/ concrete Batch mix plant (Pan mixer) excetra complete. With fine aggregate (Natural Sand / Crushed sand VSI Grade finely washed etc) (For Ground Floor) (using ARTIFICIAL SAND).	CU.M	13042.2

Scanned with OKEN Scanner

80	Providing and laying in situ/Ready Mix cement concrete M-20 of trap/ granite/ quartzite/ gneiss metal for reinforced cement concrete work in foundations like raft, strip foundations, grillage and footings of reinforced cement concrete columns and steel stanchions, excetra including bailling out water, formwork, cover blocks, compaction, curing and roughening the surface if special finish is to be provided (Excluding reinforcement and structural steel), excetra complete, with fully automatic micro processor based Programmable Logic Controller without Supervisory Control and Data Aquisition enabled reversible Drum Type mixer/ concrete Batch mix plant (Pan mixer) excetra complete. With fine aggregate (Natural Sand / Crushed sand VSI Grade finely washed etc) (using ARTIFICIAL SAND).	CU.M	7843.35
81	Providing and laying in situ/Ready Mix cement concrete M-15 of trap metal for reinforced cement concrete work in foundations like raft, strip foundations, grillage and footings of reinforced cement concrete columns and steel stanchions, excetra including bailling out water, formwork, cover blocks, compaction, curing and roughening the surface if special finish is to be provided (Excluding reinforcement and structural steel), excetra complete, with fully automatic micro processor based Programmable Logic Controller without Supervisory Control and Data Aquisition enabled reversible Drum Type mixer/ concrete Batch mix plant (Pan mixer) excetra complete. With natural sand/V.S.I. quality Artificial Sand (using ARTIFICIAL SAND).	CU.M	7528.65
82	Providing and fixing hume pipe septic tank 900 milimetre diameter with vent pipe and cap including excavation and laying.	NO	17545.55
83	Hire charges for Crane - 20 tonne capacity at the site of work	HOUR	2413.95
84	Hire charges for Generator 33 kVA at the site of work.	HOUR	515.55
85	Removing doors and windows with frames and stacking the materials as directed with all leads, lifts excetra complete.	NO	163.65
86	Removing ventilators and small windows with frame and stacking the materials with all leads lifts excetra complete.	NO	138.45
87	Providing and laying 125 micron low density polyethylene sheet confirming to Indian Standard : 3395 - 1997 below concrete pavement including all materials and labour complete.	SQ.M	31.45
88	Providing and fixing 1.5 milimetre thick polyvinyl chloride flooring including levelling the base with white cement including pasting with appropriate material, cleaning the surface, excetra complete.	SQ.M	672.4
89	Providing and fixing in position (as per Indian Standard : 1868/1982) aluminium sliding window of two tracks with rectangular pipe having overall dimentsions 63.50 milimetre X 38.10 milimetre X 1.02 milimetre at weight 0.547 kilogram per running metre and window frame bottom track section 61.85 milimetre X 31.75 milimetre X 1.20 milimetre at weight 0.695 kilogram per running metre. Top and side track section 61.85 milimetre X 31.75 milimetre X 1.30 milimetre at weight 0.659 kilogram per running metre. The shutter should be of bearing bottom 40 milimetre X 18 milimetre X 1.25 milimetre at weight 0.417 kilogram per running metre. Interlocking secion 40 milimetre X 18 milimetre X 1.10 milimetre at weight 0.469 kilogram per running metre and handle section 40 milimetre X 18 milimetre X 1.25 milimetre at weight 0.417 kilogram per running metre and top section 40 milimetre X 18 milimetre X 1.25 milimetre at weight 0.417 kilogram per running metre as per detailed drawing and as directed by Engineer in-charge with all necessary aluminium sections, fixtures and fastenings such as roller bearing in nylon casting and self locking catch fitted in vertical section of shutter including 5 milimetre thick plain glass with all required screws and nuts excetra complete. - With powder coating with box. (For Ground Floor)	SQ.M	5542.9
90	Providing and fixing in position (as per Indian Standard : 1868/1982) aluminium sliding window of three tracks with rectangular pipe having overall dimentsions 95 milimetre X 38 milimetre X 0.90 milimetre at weight 0.637 kilogram per running metre and window frame bottom track section 92 milimetre X 31.75 milimetre X 1.30 milimetre at weight 1.070 kilogram per running metre. Top and side track section 92 milimetre X 31.75 milimetre X 1.30 milimetre at weight 0.933 kilogram per running metre. The shutter should be of bearing bottom 40 milimetre X 18 milimetre X 1.25 milimetre at weight 0.417 kilogram per running metre. Interlocking secion 40 milimetre X 18 milimetre X 1.10 milimetre at weight 0.469 kilogram per running metre and handle section 40 milimetre X 18 milimetre X 1.25 milimetre at weight 0.417 kilogram per running metre and top section 40 milimetre X 18 milimetre X 1.25 milimetre at weight 0.417 kilogram per running metre as per detailed drawing and as directed by Engineer in-charge with all necessary aluminium sections, fixtures and fastenings such as roller bearing in nylon casting and self locking catch fitted in vertical section of shutter including 5 milimetre thick plain glass and aluminium mosquito net shutter with stainless steel jali with all required screws and nuts excetra complete. - With colour anodising without box. (For Ground Floor)	SQ.M	5690.85
91	Providing and fixing steel window/door of various sizes as per detailed drawing without hot dip zinc coating, without ventilators, including fabricating / glazing with plain / obscured glass panels of approved type and quality, iron oxidised fixtures and fastenings, finishing with oil painting two coats, excetra complete. (with guard bars 12 milimetre square at 10 centimetre center to centre.) (For Ground Floor) (For Ground Floor)	SQ.M	5112.85

Scanned with OKEN Scanner

92	Providing and fixing mild steel grill work for windows, ventilator, excetra 20 kilogram per square metre as per drawings including fixtures, necessary welding and painting with one coats of anticorrosive paint and two coats of oil painting, excetra complete. (For Ground Floor)	SQ.M	2199.75
93	Providing and fixing crimped wire galvanised iron mesh of size 20 milimetre X 20 milimetre, 10 gauge to iron angle frame including welding crimp mesh to angle frame and steel flat, fixing the frame in its origional position and oil painting, excetra complete. (Excluding cost structural steel) (For Ground Floor)	SQ.M	806.7
94	Providing and fixing mild steel grill gate as per the detailed drawing including hinges, locking arrangements and painting in three coats of oil paint of approved colour and shade, excetra complete. Weight 18 to 20 kilogram per Square metre. (For Ground Floor)	SQ.M	2202.9
95	Providing and fixing rolling shutter fabricated from steel laths of minimum thickness 0.9 milimetre with lock plate of 3.15 milimetre thickness reinforced with 35 milimetre X 35 milimetre X 5 milimetre angle section fitted with sliding bolts and handles for both sides, deep mild steel channel section of depth and thickness not less than 65 milimetre and 3.15 milimetre respectively with hold fast arrangements, mild steel bracket plate 300 milimetre X 300 milimetre X 3.15 milimetre minimum size and shape with square bar, suspension shaft of minimum 32 milimetre diametre, hood cover of mild steel sheet not less than 0.9 milimetre thickness and of any size at top and safety devices including mechanical gear operation arrangement consisting of worm gear wheels and worms of high grade cast iron or mild steel and one coat of red lead primer, excetra complete. (Indian Standard : 6248-1979) - without mechanical gear	SQ.M	5065.6
96	Providing And Fixing Stainless Steel Handle for door	NO	74
97	Water Pump Motor	NO	5000
98	Providing And Fixing Precast Rcc Cover (90*45 cm)	NO	4271.55
99	Providing and Fixing Projector Curtain of Appropriate colour and design with all necessary fittings including all lead,lift etc complete	SQ.M	145.69
100	Creating and fitting the logo of Ichalkaranji Municipal Corporation on acrylic design	NO	13760
101	Gypsum board false celling	SQ.M	1432
102	Precast Compound wall	SQ.M	100
103	Providing and fixing 900 milimetre high, stainless steel 304 grade stainless steel railing with 40 milimetre diameter and 1.5 milimetre thick at top, 40 milimetre diameter and 1.5 milimetre thick verticle supports spaced at 1.5 metre center to center and 8 milimetre thick toughened glass including fabricating, fixtures, errecting, necessary welding, grinding, finishing, buffing to stainless steel pipe, excetra complete. (For Ground Floor)	RMT	4934.5
104	window Net Mesh	SQ.M	24.28

तरी सदस्य स्वेच्छा निधीतून इचलकरंजी महानगरपालिका शौचालय / गटर / इमारती रंगरंगोटी / शाळा / व्यायाम शाळा साहित्य दुरुस्ती करणे व इतर अनुषंगीक विकास कामे करणे करीता एकूण १०४ बाबींचे रु. ७,३२,५०,०००/- चे करणेत आलेले अंदाजपत्रकास (Rate Contract) मंजुरी देणेत येत आहे.

सूचक : सु.बा.कळगते

अनुमोदक : र.ला.टजपुते.

ठराव सर्वानुमते मंजुर

सभापती
स्थायी समिती

Scanned with OKEN Scanner

इचलकरंजी महानगरपालिका

मा. स्थायी सभा क्र.०६

स्था. स. ठराव क्र. ३४
दि. ०६/०७/२०२६

विषय क्र. ३ : इचलकरंजी महानगरपालिका हद्दीमधील दैनंदीन बाजार फी, मंडप / स्टॉल भाडे वसुली मक्ता देणेकामी आधारभुत किंमत १,३१,५६,०००/- याजवर दोन वेळा निविदा मागविणेत आली असता निविदेस प्रतिसाद मिळत नसलेने उत्पन्न वाढीचे दृष्टीने सन २०२३-२४ या सालामधील धरलेली आधारभुत किंमत रु. ९४,००,०००/- गृहीत धरुन नव्याने निविदा प्रसिद्ध करणेस मंजुरी मिळणेबाबत कार्यालयाकडुन आलेला प्रस्ताव.

ठराव

इचलकरंजी महानगरपालिका हद्दीमधील सन २०२५-२६ व २०२६-२७ या कालावधी करिता दैनंदिन बाजार फी, मंडप /स्टॉल भाडे इ. वसुली मक्ता देणे कामी आधारभूत किंमत रु. १,३१,५६,०००/- एवढ्या किंमतीने ई-निविदा दि. २९/१०/२०२५ ते दि. ११/११/२०२५ अखेर मागविण्यात आली होती मात्र या कालावधीत केवळ १ निविदा प्राप्त झाली असल्याने दि. १७/११/२०२५ पर्यंत प्रथम मुदत वाढ देण्यात आली. मात्र याही कालावधीत १ निविदा प्राप्त झाले असल्याने दि. २५/११/२०२५ पर्यंत दुसरी मुदत वाढ देण्यात आली. सदर ई – निविदेस २ (दोन) वेळेस मुदत वाढ देऊन हि केवळ २ ई – निविदाच प्राप्त झाल्या आहेत.

मात्र संबंधितांनी मुदतीत इकडे कागदपत्रे सदर केली नाहीत. त्यामुळे दोन्ही ई-निविदा धारक हे अपात्र झाले. सदर रक्कमेवर ई-निविदा प्रसिद्धी करून व २ वेळा मुदत वाढ देऊन हि ई-निविदेस प्रतिसाद मिळाला नाही.

उत्पन्न वाढीच्या दृष्टीने सन २०२३-२४ या सालामधील आधारभूत धरलेली किंमत ९४,००,०००/- यावर सन २०२४-२५ १०% व सन २०२५-२६ १०% वाढ करून रक्कम रु. १,१३,७४,०००/- इतकी आधारभूत किंमत निश्चित करुन स्थायी स. ठराव क्र. ०४ दि. २७/०३/२०२६ चे मंजुरीनुसार जाहीर ई-निविदा प्रसिद्ध करण्यात आली होती. ई-निविदा दि. १५/०५/२०२६ ते २६/०५/२०२६ अखेर जाहीर प्रसिद्धी केली होती. मात्र मुदती अंती एकही ई-निविदा प्राप्त झालेली नाही.

मा. आयुक्त यांच्या मान्यतेने म.न.पा च्या उत्पन्न वाढीच्या दृष्टीने दि. ०९/०६/२०२६ दु. ०२.०० अखेर ई-निविदेची दुसरी वेळ देण्यात आली. परंतु मुदतीअंती केवळ एकाच (१) निविदा प्राप्त झाली आहे.

दरम्यानच्या काळात मुख्य रस्त्यावरील सर्व अतिक्रमण धारक / हातगाडी धारक, भाजीपाला व्यापारी, विक्रेते यांना दि. २१/०४/२०२६ पासून आजअखेर हटविण्यात आले आहे. तसेच इचलकरंजी व्यंकोबा मैदान या ठिकाणी गणेशोत्सव काळात भरणारा फेस्टिव्हल (मनोरंजन खेळणी) व दिवाळी सणानिमित्त मुख्य रस्तावर भरणारा बाजार या बाबत नागरिकांच्या तक्रारी इकडे प्राप्त होत आहेत. या पासून मिळणारे उत्पन्नाची अनिश्चिता आहे.

तसेच सध्या पावसाळ्याचे दिवस आहेत. ७ ते ८ कर्मचारी वसुली कामी कार्यरत असून ठेका गेलेस सदरचे कर्मचारी ऑफिसकडे कार्यरत राहतील व उत्पन्न वाढीच्या दृष्टीने सन २०२३-२४ या सालामधील धरलेली आधारभूत किंमत रु. ९४,००,०००/- इतकी रक्कम गृहीत धरून नव्याने निविदा प्रसिद्ध करण्यास व मागील रक्कम रु. १,१३,७४,०००/- ची ई-निविदा रद्द करणेस मंजुरी मिळणेकामी कार्यालयाने प्रस्ताव सादर केला आहे.

तरी कार्यालयीन प्रस्तावानुसार इचलकरंजी महानगरपालिका हद्दीमधील दैनंदीन बाजार फी, मंडप / स्टॉल भाडे वसुली मक्ता देणेकामी आधारभुत किंमत १,३१,५६,०००/- याजवर दोन वेळा निविदा मागविणेत आली असता निविदेस प्रतिसाद मिळत नसलेने उत्पन्न वाढीचे दृष्टीने सन २०२३-२४ या सालामधील धरलेली आधारभुत किंमत रु. ९४,००,०००/- गृहीत धरुन नव्याने निविदा प्रसिद्ध करणेस मंजुरी देणेत येत आहे.

सूचक : सु. बा. कलगते अनुमोदक : र. ला. रजपुते.

ठराव सर्वानुमते मंजुर

सभापती
स्थायी समिती

इचलकरंजी महानगरपालिका

Scanned with OKEN Scanner

इचलकरंजी महानगरपालिका

मा. स्थायी सभा क्र.०६

स्था. स. ठराव क्र. ३५
दि. ०६/०७/२०२६

विषय क्र. ४ : इचलकरंजी महानगरपालिकेकडे रोगजंतुनाशके व औषधी द्रव्ये यांचा पुरवठा करणे अंदाजपत्रक र. रु. १,०१,४०,०००/- व इचलकरंजी महानगरपालिकेकडे रोगजंतुनाशके / डास अळी नाशके / किटकनाशके व औषधी द्रव्ये यांचा पुरवठा करणे अंदाजपत्रक र. रु. ४८,८६,८००/- यास मंजुरी देणेबाबत कार्यालयाकडुन आलेला प्रस्ताव.

ठराव

इचलकरंजी महानगरपालिकेकडे रोगजंतू नाशके व औषधी द्रव्ये यांचा पुरवठा करणेचे अंदाजपत्रकीय रक्कम रुपये र.रु.१,०१,४०,०००/- (एक कोटी एक लाख चाळीस हजार रुपये) आणि रोगजंतू नाशके/ डासअळी नाशके/किटक नाशके व औषधी द्रव्ये यांचा पुरवठा करणेचे अंदाजपत्रकीय रक्कम ४६,८६,८००/-(सेहचाळीस लाख शहाऐंशी हजार आठशे रुपये) अशा एकूण र.रु.१,४८,२६,८००/- (एक कोटी अठ्ठेचाळीस लाख सव्वीस हजार आठशे रुपये) इतक्या अंदाजपत्रकीय रक्कमेस आणि या दोन कामांसाठी दोन स्वतंत्र जाहिर ई-निविदा प्रसिध्द करणेसाठी मे.स्थायी समितीची मंजुरी मिळणेसाठी कार्यालयाने प्रस्ताव सादर केला आहे.

तरी इचलकरंजी महानगरपालिकेकडे रोगजंतुनाशके व औषधी द्रव्ये यांचा पुरवठा करणे अंदाजपत्रक र. रु. १,०१,४०,०००/- व इचलकरंजी महानगरपालिकेकडे रोगजंतुनाशके / डास अळी नाशके / किटकनाशके व औषधी द्रव्ये यांचा पुरवठा करणे अंदाजपत्रक र. रु. ४८,८६,८००/- यास मंजुरी देणेत येत असुन दोन कामांसाठी दोन स्वतंत्र जाहिर ई-निविदा प्रसिध्द करणेसही मंजुरी देणेत येत आहे.

सूचक : नि. कि. पोवार.

अनुमोदक : सु. वा. कलगते.

ठराव सर्वानुमते मंजुर

सभापती
स्थायी समिती

Scanned with OKEN Scanner